Experiment 26 Reflection and Refraction

Advanced Reading:

University Physics Vol.3 by OpenStax, Chapter 1 Section 1.2-1.4 and Chapter 2 Section 2.1.

Equipment:

1 Plexi-Ray kit

2 corkboards

2 protractors

2 30 cm rulers

Objective:

The object of this experiment is to study the phenomena of reflection, virtual image formation, refraction and total internal reflection.

Theory:

The **Law of Reflection** states that the angle of the incident ray equals the angle of the reflected ray, or $\theta_i = \theta_r$. See Figure 26-1. In this experiment the formation of a virtual image by a plane mirror will examined. A virtual image is an image that cannot be projected on a screen, but the image can be seen by the eye (e.g., the image from a plane mirror).




Figure 26 -1

In general the speed of light in any material is less that the speed of light in a vacuum, so the index of refraction defined as the ratio

$$n \equiv \frac{speed \text{ of } light \text{ in } vacuum}{speed \text{ of } light \text{ in medium}} = \frac{c}{v}$$

and is always greater than or equal to one.

The Law of Refraction (Snell's Law) relates how a ray of light will behave when passing from one media to the other. It is given by

$$n_1 \sin \theta_1 = n_2 \sin \theta_2$$
 Eq. 26-1



Optical ray kit used in lab

where n_1 and n_2 are the indices of refraction for the two different media and θ_1 and θ_2 are the angles measured with respect to a line normal to the interface. If $n_1 < n_2$ the refracted ray bends towards the normal. See Figure 26-2.





Figure 26-2 (Image from A+ Physics webpage)

If $n_1 > n_2$ the refracted ray bends away from the normal.

When light travels from one media to another some of the light is transmitted and some of the light is reflected. See Figure 26-3. Notice in both cases (i.e., flashlight in air and flashlight in water) there is a refracted ray and there is a reflected ray.



In figure 26-3 (a) the light from the flashlight travels **from** a material (air) with a lower index of refraction **to** a material of a higher index of refraction. In figure 26-3 (b) the light travels from a material (water) with higher index of refraction to a material of a lower index of refraction (air).

The figure above implies that the incident ray can be increased to some angle where the refracted light is perpendicular to the normal. This angle is called the critical angle. See Figure 26-4. When the incident angle is greater than the critical angle there are no refracted rays and this phenomena is called **total internal reflection.** See rightmost image in Figure 26-4.




Figure 26-4

The **critical angle** θ_c is given by the relationship

$$\theta_c = \sin^{-1} \frac{n_2}{n_1}$$
 Eq. 26-2


where in fig. 26-4, $n_2 = \text{index of refraction of air}$ and $n_1 = \text{index of refraction of water.}$ Please note this relationship is only valid when $n_1 > n_2$.

Procedure: Part 1: Reflection

1. Draw a horizontal line approximately 20 cm long at the center of a sheet of clean, white paper. (i.e., Bisect the paper perpendicular to its length) This will be the baseline. Draw another line perpendicular to the first line using the protractor & ruler. This will be your normal line.

Place the plane mirror into the slots of a holder from the Plexi-Ray kit so that it will stand-up. Next, place the mirror so that the <u>back</u> (i.e., the reflecting surface) is on the first line.

2. Draw a ray on the left side of the normal line as you face the mirror that is at least 20 cm long from the point where the normal line joins the baseline. Stick two pins vertically on the line, one approximately 20 cm and the other at approximately 10 cm from the mirror along the line. Label these points P₁ and P₂ respectively. (See figure 26-5)




3. Look at the mirror from the right side of the normal so that you can see the reflection of the first two pins. Stick two pins into the paper so that they appear to be co-linear to the first two pins. Label these two points P₃ and P₄. It is important that the mirror not move from the baseline. This will change the angle of reflection.

- 4. Draw a line that connects points P₃ and P₄. Measure the angle of incidence and the angle of reflection and compare to theory.
- 5. Repeat steps 2-4 for another set of points.

Part 2: Refraction.


6. Place the plexiglass (or glass square) at the center of another sheet of clean white paper and trace around it. In the upper-left corner of the traced square, draw a line normal to the square 1 cm from the corner of the square that crosses the side of the square. (see figure 26-6).



- 7. Draw a line left of the normal and place pins on the line as done in part 1 of this experiment. Look through the plexiglass square from the side opposite pins and place pins two pins in the page so that it appears that all the pins are collinear. Label these two points P₃ and P₄. Take the pins out and draw a line through the points beginning at the edge of the square. Where the line joins the edge of the square, draw another normal line that crosses the side of the edge of the square.
- 8. Measure the angles that the incident and transmitted (refracted) ray makes to the normal N when the ray enters the block. Repeat these measurements for the ray as it leaves the block. Use these angles to calculate the index of refraction of the material. See Figure 26-6.
- 9. Repeat for a different set of points.

Part 3 Total Internal Reflection

10. Place the plexiglass triangle on a sheet of paper and trace around the edges. Put two pins in the page at points P_1 and P_2 such that the line defined by the 2 points is perpendicular to the base of the triangle. (See Figure 26-7)



P₂

figure 26-7

11. Stick two more pins into the page so that all four pins appear co-linear. Remove the triangle from the page and draw rays showing the path of the light ray. (The result may be surprising.)

Part 4 Image from a plane mirror

- 12. The image seen in any plane mirror does not appear to be at the surface of the mirror, but rather, to be located some distance behind the surface This image is known as a virtual image. The image appears to be located the same distance behind the mirror as the object is in front of the mirror. (See figure 26-8)
- 13. Draw a line bisecting a sheet of clean, white paper. Place the triangular plexiglass in the middle of one of the bisected halves and trace around it. **Remove the triangular piece.** Label the vertices A, B, C. Place the mirror on the line bisecting the paper with the silvered surface exactly on the line. See figure 26-8.

- 14. Stick a pin into the cork board at the vertex labeled A and from a point of observation, use two more pins to mark a sight line to the image of the point A pin. Remove the sighting pins and mark the pin pricks with an 'a'. Repeat this again from a different observation point. Do this again for the pins a vertices B and C, obtaining two sight lines for each vertex. (see figure 26-8)
- 15. Remove all the pins and the mirror. Draw a line connecting the first two 'a' pin pricks, extending the line fully across the page. Do this for all pairs of pin pricks. Mark the intersection of the 'a' lines with an A' and the intersection of the 'b' and 'c' lines with a B' and C' respectively.
- 16. Connect the point A', B', and C'. Measure the dimensions of the virtual image and compare the dimensions with the object triangle.

